


SG0610T1(6V1.0AH)




Outer dimensions (mm)



Specifications

Nominal Voltage		6 V
Rated capacity (20 hour rate)		1.0 Ah
Dimensions	Total Height	56mm(2.20 inches)
	Height	51 mm(2.01 inches)
	Length	51 mm(2.01 inches)
	Width	42 mm(1.65inches)
Weight Approx		0.26Kg(0.57lbs)


Terminal Type (mm)



Characteristics

Capacity 25 °C (77 °F)		20 hour rate(0.05A)	1.0 AH
		10 hour rate(0.092A)	0.92AH
		5 hour rate(0.17A)	0.85 AH
		1 hour rate(0.60A)	0.60AH
		1.5 hour discharge to 5.25 V	0.43A
Internal Resistance		Full charged Battery at 25°C(77°F)	60 m Ω
Capacity affected by Temperature (20hour rate)		40°C(104°F)	102%
		25°C(77°F)	100%
		0°C(32°F)	85%
		-15°C(5°F)	65%
Self-Discharge at 25°C(77°F)		Capacity after 3 month storage	91%
		Capacity after 6 month storage	82%
		Capacity after 12 month storage	64%
Terminal		T1	
Charge (constant Voltage)	Cycle	Initial Charging Current less than 0.3 A Voltage 7.20-7.35 V	
	Float	Voltage 6.75-6.90 V	

Discharge Curves 25 °C(77°F)



Constant Current(Amp) and Constant Power(Watt) Discharge Table at 25 °C(77°F)

Time	5min	10min	15min	30min	1h	2h	3h	4h	5h	8h	10h	20h
4.80V	A 3.60	2.26	1.75	1.15	0.60	0.35	0.26	0.21	0.18	0.12	0.09	0.05
	W 21.2	13.3	10.1	6.1	3.5	2.0	1.49	1.20	1.01	0.67	0.55	0.30
5.10V	A 3.30	2.21	1.61	1.09	0.56	0.34	0.25	0.20	0.17	0.11	0.93	0.05
	W 20.0	13.1	9.5	6.1	3.3	1.9	1.45	1.16	1.00	0.66	0.54	0.29
5.25V	A 3.06	2.11	1.50	1.06	0.55	0.33	0.25	0.19	0.17	0.11	0.09	0.05
	W 19.3	12.3	9.1	6.0	3.2	1.9	1.42	1.10	0.99	0.65	0.53	0.29
5.40V	A 2.79	2.02	1.40	1.01	0.53	0.32	0.24	0.19	0.16	0.11	0.09	0.05
	W 18.4	11.9	8.7	6.0	3.1	1.9	1.41	1.09	0.95	0.63	0.52	0.28
5.55V	A 2.41	1.90	1.30	0.94	0.51	0.31	0.23	0.18	0.16	0.11	0.09	0.05
	W 14.4	11.5	8.3	5.9	3.0	1.9	1.36	1.08	0.93	0.60	0.51	0.28