



Sigma Power Systems

SG1250T1 & SG1250T2 (12V 05.0Ah)

This product is a general purpose rechargeable battery Sealed Lead Acid (SLA) Technology. It is also called Valve Regulated Lead Acid (VRLA) battery. The design life is 5 years at 25 C (77°F) when used under normal operating conditions. Higher temperatures, higher charging voltage, storing at lower state of charge are some of the factors affect the life of the SLA battery. Capacity will vary depending on the temperature. Check the graphs below for details. Always follow the safety instructions while handling the battery.

Specification

Cells per Unit	6
Voltage per cell/battery	2/12 V
Capacity	5.0 Ah at 20 hr.-rate to 1.75V per cell at 25°C
Weight	Approximately 1.55 KG/3.42 lbs. (Tolerance $\pm 3\%$)
Maximum Charge Current	1.50 A
Operating Temperature Range	Discharge: -20°C ~ 60°C Charge: 0°C ~ 50°C Storage: -20°C ~ 60°C
Nominal Operating Temperature Range	25 $\pm$ 5°C
Float Charge Voltage	13.6 to 13.8 VDC/unit Average at 25°C
Maximum Discharging Current Limit	50 Amp (5 seconds)







Equalization and Cycle Service	14.6 to 14.8 VDC/unit Average at 25°C
Self Discharge	Self-discharge ratio less than 3% per month at 25°C. Please charge batteries before using.
Terminals	F1 & F2 (T1 & T2)
Jar Material	A.B.S UL94-HB

Physical Dimensions: in (mm)

Dimensions

Unit: mm Dimension: 90(L)×70(W)×107(H)





Sigma Power Systems

SG1250T1 & SG1250T2 (12V 05.0Ah)

Use this chart to estimate the current for various times and end of discharge of voltages (EDV)

Constant Current Discharge Characteristics: Amp (25°C)


EDV	5 Min.	10 Min.	15 Min.	30 Min.	1 Hr.	2 Hr.	3 Hr.	5 Hr.	8 Hr.	10 Hr.	20 Hr.
9.60 V	20.53	13.43	10.55	5.965	3.585	2.107	1.464	0.956	0.587	0.515	0.290
10.0 V	19.75	13.15	10.23	5.895	3.495	2.101	1.447	0.938	0.585	0.510	0.283
10.2 V	19.54	12.85	10.02	5.807	3.468	2.084	1.434	0.928	0.580	0.507	0.278
10.5 V	17.65	12.05	9.774	5.668	3.407	2.058	1.422	0.918	0.578	0.505	0.270
10.8 V	15.98	11.88	9.265	5.587	3.352	2.043	1.407	0.909	0.576	0.501	0.268
11.1 V	14.96	11.05	8.684	5.385	3.296	2.003	1.395	0.901	0.575	0.500	0.260

Use this chart to estimate the power for various times and end of discharge voltages (EDV)


Constant Power Discharge Characteristics: Watt (25°C)

EDV	5 Min.	10 Min.	15 Min.	30 Min.	1 Hr.	2 Hr.	3 Hr.	5 Hr.	8 Hr.	10 Hr.	20 Hr.
9.60 V	215.88	143.78	113.65	68.96	42.23	25.12	17.34	11.98	7.85	6.75	3.854
10.0 V	210.31	141.83	112.56	67.78	41.57	24.91	17.30	11.93	7.62	6.37	3.735
10.2 V	201.14	136.72	110.79	67.15	41.23	24.76	17.24	11.81	7.60	6.28	3.664
10.5 V	187.85	130.86	105.83	66.45	40.84	24.53	17.10	11.68	7.55	6.25	3.605
10.8 V	169.64	122.73	100.54	64.78	40.32	24.37	16.99	11.54	7.25	6.17	3.435
11.1 V	150.32	117.98	94.87	64.08	39.65	23.67	16.38	11.49	6.98	6.05	3.387


Temperature and Valid Capacity




Charge Characteristics for Float Use @ 25°C/77°F



Discharge Characteristics at Various Rates @ 25°C/77°F



Cycle Life in Relation to Depth of Discharge





Sigma Power Systems

SG1250T1 & SG1250T2 (12V 05.0Ah)

Capacity at Different Temperatures

Battery Type		-20°C	-10°C	0°C	5°C	10°C	20°C	25°C	30°C	40°C	45°C
GEL Battery	6V & 12V	50%	70%	83%	85%	90%	98%	100%	102%	104%	105%
	2V	60%	75%	85%	88%	92%	99%	100%	103%	105%	106%
AGM Battery	6V & 12V	46%	66%	76%	83%	90%	98%	100%	103%	107%	109%
	2V	55%	70%	80%	85%	92%	99%	100%	104%	108%	110%

Discharge Current Vs. Discharge Voltage

Final Discharge Voltage V/cell	1.75V	1.70V	1.60V
Discharge Current (A)	$A \leq 0.2C$	$0.2C \leq A \leq 1.0C$	$\geq 1.0C$

Safety & Maintenance Tips

❗ Do not charge the battery in air tight atmosphere.

❗ Do not short the terminals.

❗ Avoid leaving them in hot environment.

❗ Charge the batteries at least once in 6 months when the batteries are at 77°F

❗ Max. charge current 0.3CA, constant voltage 2.4-2.45V/Cell charge 24h

❗ Effect of temperature on float charge voltage: -3mV/Cell.

❗ Life will be reduced by number and depth of discharge.

❗ Do not discharge below the minimum recommended voltage.

❗ Leaving a discharged battery without charge for a long period of time will affect the life of the batteries.

Charging Method

Constant Voltage	$-0.2C \times 2h + 2.4 - 2.45V/\text{cell} \times 24h$, Max. Current 0.3CA
Constant Current	$-0.2C \times 2h + 0.1CA \times 12h$
Fast	$-0.2C \times 2h + 0.3CA \times 4.0h$

General applications – Emergency lights, solar, UPS, Alarm systems, Security systems, wheelchairs, flash lights, toys etc.

Charge the batteries at least once every six months, if they are stored at 25°C

www.sigmapowersystems.com



506 Business Pkwy,
Richardson, TX 75081
(877) 394-3941
info1@sigmapowersystems.com